




Type	Upright
Volume total	750 litre
Usable volume 2/4 compartments	700/691 litre
Storage capacity 2" boxes	576
External dimensions	1140/1195 x 888 x 1999,5 mm
Internal dimensions	890 x 626,5/592 x 1345 mm
Compartments/inner doors/platforms	4/2/3 in height adjustable
Main door	With lock and keys
Inner doors	Stainless steel, insulated
Material internal/external	Stainless Steel/Epoxy Coated steel
Placed on	Heavy duty castors with levelling feet
Insulation	Polyurethane
Cooling	Two (2) cascade connected inverter compressors
Refrigerants	First stage: R290/Second stage: R170
Condenser	Air-cooled
Temperature adjustments	-50°C till -86°C (other range; on request)
Controller	Web-based
Display	7" Touchscreen in main door at eye level
Temperature history	On display with scroll function
Data storage	At least 12 months
Temperature sensors	PT1000
Backup battery	Alarming and monitoring during power failure
Alarming	Optical and acoustic, but also possible via E-Mail
Communication	Telephone dialling activation system Potential (Voltage) free contact RJ45 (Ethernet) connection USB connection
Software	I-freeze
CO ₂ -backup system	Partially prepared
Transit/vacuum release	Ø 26 mm/vacuum release situated in transit
Cable entry ports	Two (2)
Compressor room	Well-arranged layout and very easy filter exchange
Requirements	220/240 VAC, 50 Hz, fuse 16 Amp. slow
Power and current rating	465 VA/410 W/2,9 Amp.
Energy consumption (Setpoint -80°C)	8,9 kWh/24h
Heat exchange	6,675 kW/24h - 0,278 kW/h
Noise level	49 dBA
Net weight	380 kg
CE certified	EN61010-1:2010, EN60601-1-2:2007

OPTIONS

- Hybride Cooling System
- Water cooling
- CO₂-backup system
- LN₂-backup system
- Extended backup system
- Temperature chart recorder
- Voltage stabilizer
- Transformer
- IQ/OQ/PQ
- Electronic lock main door
- Padlock on main door
- Left hinged door(s)
- 3, 4, 5 or 6 compartments/inner doors
- Inner doors lockable by key
- Alarming by texting and/or phone
- Sliding shelves with hinged front
- Drawers in Aluminium or Stainless Steel
- Racking systems in Aluminum or Stainless Steel
- Cryo Boxes
- Cryo Gloves



DRAWER RACKING SYSTEM*1



Model #	Comp.	# Racks	# Boxes per rack	Total boxes 133x133	Total plates 128x85	Max. height box
DSA-8336-136G	4	24	48		1152/1344 ^{*2}	33 mm
DSA-5504-136G	4	6	20	552 ^{*2}	828/966 ^{*2}	50 mm
DSA-6504-136G		18	24			
DSA-12504-136G	2	12	48	576	864/1008 ^{*2}	50 mm
DSA-D212504-136G	2	6	96	576	864/1008 ^{*2}	50 mm
DSA-5534-136G	4	12	20	528 ^{*2}	792 / 924 ^{*2}	53 mm
DSA-6534-136G		12	24			
DSA-7844-136G	2	12	28	336		84 mm
DSA-D27844-136G	2	6	56	336		84 mm
DSA-31004-136G	4	24	12	288		100 mm
DSA-21284-136G	4	24	8	192		128 mm

*1 other dimensions on request. *2 only on request.

SIDE ACCESS RACKS

Model #	Comp.	# Racks	# Boxes per rack	Total boxes 133x133	Maximum height box
HR-4-6-45	4	24	24	576	45 mm
HR-4-5-53	4	24	20	480	53 mm
HR-4-3-76	4	24	12	288	76 mm
HR-5-FLEX	4	24	20/12	480/288	55/95 mm

Laurent Janssensstraat 105
5048 AR Tilburg
The Netherlands
T +31 13 750 15 55
F +31 13 463 86 35
info@snijderslabs.com
www.snijderslabs.com

